

AQUABATCH™/AQUADRAIN™
Eliminates Hair, Lint and Sand



PRODUCT
QUALITY



BRAND
PROTECTION



WATER



WASTE



Eliminate hair, lint and sand. Increase customer satisfaction with the powerful combination of AquaBatch™/AquaDrain™

The AquaBatch is a filter system specially designed to remove hair, lint and sand out of tunnel washers. Water is pumped out of the rinse zone at the lowest point, filtered, and transferred back into the same compartment.

The AquaDrain is a bag filtration system used to filter the back flush water from the AquaBatch. An oscillating filter bag removes the solid particles from the back flush water reducing the amount of lint, sand, debris and COD.

ECOLAB®

AQUABATCH™ FEATURES AND BENEFITS

- Rinsing optimization reduces water consumption
- System works automatically - automatic back flush included
- Filtration will not impact tunnel transfer rates
- High filtration capacity - 65-105 gallons/minute
- Total volume of water is filtered up to 3 times within one batch cycle
- Flexible filter sizes: 115μ, 130μ, 200μ
- Closed system for premium hygiene solution
- Low maintenance, easy installation
- Small footprint



AQUABATCH™ SPECIFICATIONS

- **Dimensions:**
31.5" long; 30.31" wide; 78.74" high
- **Voltage Requirements:**
480V - 11 amps
3 phase
60 HTZ

AQUADRAIN™ FEATURES AND BENEFITS

- Reduces lint, hair, sand and debris from drain
- COD reduction
- Single step filtration
- Moving filtration bag
- Stainless steel components
- Flexible filter sizes: 50μ, 100μ, 200μ, 400μ
- Low maintenance, easy installation
- Small footprint



AQUADRAIN™ SPECIFICATIONS

- **Dimensions:**
22" long; 28" wide; 44" high
- **Compressed Air Requirements:**
Compressed air connection: 1/4" BSP
Minimum air pressure: 6 bar
Maximum air pressure: 8 bar